FIRE & EMERGENCY SERVICES

(MUNICIPAL CORPORATION, CHANDIGARH)

APPLICATION/PERFORMA FOR OBTAINING/RENEWAL OF FIRE SAFETY NOC FOR INSTITUTIONAL BUILDINGS (HOSPITAL SANATORIA AND NURSING HOMES) LESS THAN 15 METER IN HEIGHT WITH PLOT AREA UP TO 1000 m² [UP TO GROUND + ONE STOREY, WITH NO BEDS].

Application Date-___/___/20___

	DETAIL OF BUIL	DING/PREM	ISES	
01.	Name of building premises (Location and Address)	DING/FIXEW	ISLS	
02.	Name, Address and Contact No. of Building			
03.	Owner Name, Address and Contact No. of			
	Applicant			
04.	No. of inhabitants/occupants			
05. 06.	Plot Area (in Sq. Meters)			
06. 07.	Total covered area (in Sq. Meters) Over all Height (From Ground Level to			
	Parapet) in Meters			
08.	Height upto terrace of last livable floor (in Meters).			
09.	Height of each floor (in Meters)			
10.	Number of sanctioned floors			
11.	Number of actual floors			
12. 13.	Number of staircase with size Please indicate floors to whom NOC is			
13.	required			
14.	Motorable space provided all around the building			
15.	Number of Basement and its area			
16.	Detail of Means of escape			
17.	Detail of Parking area			
18.	Details of surrounding properties:- a) Front side b) Rear side c) Right side			
19.	d) Left side			
19. 20.	d) Left side Number of entry and exit gates with size			
20.	d) Left side	ER NATIONA	AL BUIL	DING CODE OF INDIA-2016
20.	d) Left side Number of entry and exit gates with size Location of Gen-set with size	ER NATIONA YES	AL BUIL	DING CODE OF INDIA-2016 Remarks of Inspection Authority Ok or not
20. M/	d) Left side Number of entry and exit gates with size Location of Gen-set with size ANDATORY FIRE SAFETY MEASURES AS PI A) FIRE FIGHTING EQUIPMENTS Fire Extinguishers ISI Mark			Remarks of Inspection
20. M	d) Left side Number of entry and exit gates with size Location of Gen-set with size ANDATORY FIRE SAFETY MEASURES AS PI A) FIRE FIGHTING EQUIPMENTS Fire Extinguishers ISI Mark Automatic Sprinkler System required to be installed in Basement (if area of Basement			Remarks of Inspection
01. 02.	d) Left side Number of entry and exit gates with size Location of Gen-set with size ANDATORY FIRE SAFETY MEASURES AS PI A) FIRE FIGHTING EQUIPMENTS Fire Extinguishers ISI Mark Automatic Sprinkler System required to be installed in Basement (if area of Basement exceeds 200 m²)			Remarks of Inspection
20. M/	A) Left side Number of entry and exit gates with size Location of Gen-set with size ANDATORY FIRE SAFETY MEASURES AS PI A) FIRE FIGHTING EQUIPMENTS Fire Extinguishers ISI Mark Automatic Sprinkler System required to be installed in Basement (if area of Basement exceeds 200 m²) Terrace Tank over respective tower terrace capacity 5000 Liter exclusively for Firefighting purpose alongwith Pump capacity 450 LPM at the terrace tank level with minimum pressure of 3.5 Kg/cm² (if			Remarks of Inspection
01. 02.	d) Left side Number of entry and exit gates with size Location of Gen-set with size ANDATORY FIRE SAFETY MEASURES AS PI A) FIRE FIGHTING EQUIPMENTS Fire Extinguishers ISI Mark Automatic Sprinkler System required to be installed in Basement (if area of Basement exceeds 200 m²) Terrace Tank over respective tower terrace capacity 5000 Liter exclusively for Firefighting purpose alongwith Pump capacity 450 LPM at the terrace tank level with			Remarks of Inspection
01. 02. 03.	Number of entry and exit gates with size Location of Gen-set with size ANDATORY FIRE SAFETY MEASURES AS PI A) FIRE FIGHTING EQUIPMENTS Fire Extinguishers ISI Mark Automatic Sprinkler System required to be installed in Basement (if area of Basement exceeds 200 m²) Terrace Tank over respective tower terrace capacity 5000 Liter exclusively for Fire-fighting purpose alongwith Pump capacity 450 LPM at the terrace tank level with minimum pressure of 3.5 Kg/cm² (if basement area exceed 200m²) Two-Way Fire Brigade Connection with NRV in Box B) DETECTION AND ALARAM SYSTEM			Remarks of Inspection
01. 02.	d) Left side Number of entry and exit gates with size Location of Gen-set with size ANDATORY FIRE SAFETY MEASURES AS PI A) FIRE FIGHTING EQUIPMENTS Fire Extinguishers ISI Mark Automatic Sprinkler System required to be installed in Basement (if area of Basement exceeds 200 m²) Terrace Tank over respective tower terrace capacity 5000 Liter exclusively for Firefighting purpose alongwith Pump capacity 450 LPM at the terrace tank level with minimum pressure of 3.5 Kg/cm² (if basement area exceed 200m²) Two-Way Fire Brigade Connection with NRV in Box	YES	NO	Remarks of Inspection Authority Ok or not Remarks of inspection
01. 02. 03.	Number of entry and exit gates with size Location of Gen-set with size ANDATORY FIRE SAFETY MEASURES AS PI A) FIRE FIGHTING EQUIPMENTS Fire Extinguishers ISI Mark Automatic Sprinkler System required to be installed in Basement (if area of Basement exceeds 200 m²) Terrace Tank over respective tower terrace capacity 5000 Liter exclusively for Firefighting purpose alongwith Pump capacity 450 LPM at the terrace tank level with minimum pressure of 3.5 Kg/cm² (if basement area exceed 200m²) Two-Way Fire Brigade Connection with NRV in Box B) DETECTION AND ALARAM SYSTEM Manually Operated Electronic Fire Alarm System C) EVACUATION PROVISIONS	YES	NO	Remarks of Inspection Authority Ok or not Remarks of inspection
01. 02. 03.	Number of entry and exit gates with size Location of Gen-set with size ANDATORY FIRE SAFETY MEASURES AS PI A) FIRE FIGHTING EQUIPMENTS Fire Extinguishers ISI Mark Automatic Sprinkler System required to be installed in Basement (if area of Basement exceeds 200 m²) Terrace Tank over respective tower terrace capacity 5000 Liter exclusively for Firefighting purpose alongwith Pump capacity 450 LPM at the terrace tank level with minimum pressure of 3.5 Kg/cm² (if basement area exceed 200m²) Two-Way Fire Brigade Connection with NRV in Box B) DETECTION AND ALARAM SYSTEM Manually Operated Electronic Fire Alarm System C) EVACUATION PROVISIONS	YES	NO	Remarks of Inspection Authority Ok or not Remarks of inspection Authority Ok or not Remarks of Inspection
01. 02. 03.	Number of entry and exit gates with size Location of Gen-set with size ANDATORY FIRE SAFETY MEASURES AS PI A) FIRE FIGHTING EQUIPMENTS Fire Extinguishers ISI Mark Automatic Sprinkler System required to be installed in Basement (if area of Basement exceeds 200 m²) Terrace Tank over respective tower terrace capacity 5000 Liter exclusively for Firefighting purpose alongwith Pump capacity 450 LPM at the terrace tank level with minimum pressure of 3.5 Kg/cm² (if basement area exceed 200m²) Two-Way Fire Brigade Connection with NRV in Box B) DETECTION AND ALARAM SYSTEM Manually Operated Electronic Fire Alarm System C) EVACUATION PROVISIONS	YES	NO	Remarks of Inspection Authority Ok or not Remarks of inspection Authority Ok or not Remarks of Inspection

02.	Provision of Self Closing Type Fire/Smoke			
UZ.	Check Door with Electromagnetic Hold open			
	& Coordinator having minimum 02 hour Fire			
	Resistance Rating for all compartments			
03.	Provision of Double Swing Double Leaf type			
	Doors of 2.0 meter width with coordinator in			
	corridors			
04.	Provision of minimum 2.4 meter wide Aisles,			
•	Corridor, ramps etc. for movement of			
	patients and 1.5 meter for other areas which			
	not intended for use of patients			
05.	The width of every Exit shall not be less than			
	2.0 meter			
06.	Floor surface of corridor shall not be inclined			
	at a gradient steeper than 1 in 12 to the			
	horizontal			
07.	Laboratory Room shall not exceed 100m ²			
07.	and if additional space required, the same			
00	shall be Fire Separated of 120 minute			
08.	Provision of Fire Compartment Wall at the			
	compartment intersection having Fire Door			
	with minimum 120 minute Fire Resistance			
	Rating			
09.	Provision of Illuminated type EXIT			
	Signboards at all escape routes			
	D) FIRE PREVENTION MEASURES	YES	NO	
	D) FIRE PREVENTION MEASURES	YES	NO	Remarks of Inspection
	D) FIRE PREVENTION MEASURES	YES	NO	Remarks of Inspection
04		YES	NO	Remarks of Inspection Authority Ok or not
01.	All Floors shall be suitably	YES	NO	•
01.	All Floors shall be suitably compartmented/Zone with area of each	YES	NO	•
01.	All Floors shall be suitably compartmented/Zone with area of each compartment being not more than 750 m ²	YES	NO	•
01.	All Floors shall be suitably compartmented/Zone with area of each compartment being not more than 750 m ² for non-sprinkled building/basement and	YES	NO	•
01.	All Floors shall be suitably compartmented/Zone with area of each compartment being not more than 750 m ²	YES	NO	•
01.	All Floors shall be suitably compartmented/Zone with area of each compartment being not more than 750 m ² for non-sprinkled building/basement and	YES	NO	•
	All Floors shall be suitably compartmented/Zone with area of each compartment being not more than 750 m ² for non-sprinkled building/basement and 1800 m ² for sprinkled building/basement Prohibition on storage of Flammable Liquid	YES	NO	•
	All Floors shall be suitably compartmented/Zone with area of each compartment being not more than 750 m ² for non-sprinkled building/basement and 1800 m ² for sprinkled building/basement Prohibition on storage of Flammable Liquid in Laboratories or in other area not more	YES	NO	•
02.	All Floors shall be suitably compartmented/Zone with area of each compartment being not more than 750 m² for non-sprinkled building/basement and 1800 m² for sprinkled building/basement Prohibition on storage of Flammable Liquid in Laboratories or in other area not more than 03 Liter for every 10 m²	YES	NO	•
	All Floors shall be suitably compartmented/Zone with area of each compartment being not more than 750 m² for non-sprinkled building/basement and 1800 m² for sprinkled building/basement Prohibition on storage of Flammable Liquid in Laboratories or in other area not more than 03 Liter for every 10 m² Proper provision for Disposal of Hazardous	YES	NO	•
02.	All Floors shall be suitably compartmented/Zone with area of each compartment being not more than 750 m² for non-sprinkled building/basement and 1800 m² for sprinkled building/basement Prohibition on storage of Flammable Liquid in Laboratories or in other area not more than 03 Liter for every 10 m² Proper provision for Disposal of Hazardous Material	YES	NO	•
02. 03. 04.	All Floors shall be suitably compartmented/Zone with area of each compartment being not more than 750 m² for non-sprinkled building/basement and 1800 m² for sprinkled building/basement Prohibition on storage of Flammable Liquid in Laboratories or in other area not more than 03 Liter for every 10 m² Proper provision for Disposal of Hazardous Material Staircase not arranged round a Lift Shaft	YES	NO	•
02.	All Floors shall be suitably compartmented/Zone with area of each compartment being not more than 750 m² for non-sprinkled building/basement and 1800 m² for sprinkled building/basement Prohibition on storage of Flammable Liquid in Laboratories or in other area not more than 03 Liter for every 10 m² Proper provision for Disposal of Hazardous Material Staircase not arranged round a Lift Shaft Sealing of Various Shafts/Ducts at each	YES	NO	•
02. 03. 04.	All Floors shall be suitably compartmented/Zone with area of each compartment being not more than 750 m² for non-sprinkled building/basement and 1800 m² for sprinkled building/basement Prohibition on storage of Flammable Liquid in Laboratories or in other area not more than 03 Liter for every 10 m² Proper provision for Disposal of Hazardous Material Staircase not arranged round a Lift Shaft Sealing of Various Shafts/Ducts at each floor Level with Fire Resistant Material			•
02. 03. 04. 05.	All Floors shall be suitably compartmented/Zone with area of each compartment being not more than 750 m² for non-sprinkled building/basement and 1800 m² for sprinkled building/basement Prohibition on storage of Flammable Liquid in Laboratories or in other area not more than 03 Liter for every 10 m² Proper provision for Disposal of Hazardous Material Staircase not arranged round a Lift Shaft Sealing of Various Shafts/Ducts at each floor Level with Fire Resistant Material) BE ATTAC	HED	•
02. 03. 04. 05.	All Floors shall be suitably compartmented/Zone with area of each compartment being not more than 750 m² for non-sprinkled building/basement and 1800 m² for sprinkled building/basement Prohibition on storage of Flammable Liquid in Laboratories or in other area not more than 03 Liter for every 10 m² Proper provision for Disposal of Hazardous Material Staircase not arranged round a Lift Shaft Sealing of Various Shafts/Ducts at each floor Level with Fire Resistant Material DOCUMENTS TO	D BE ATTACI	HED NO	Authority Ok or not
02. 03. 04. 05.	All Floors shall be suitably compartmented/Zone with area of each compartment being not more than 750 m² for non-sprinkled building/basement and 1800 m² for sprinkled building/basement Prohibition on storage of Flammable Liquid in Laboratories or in other area not more than 03 Liter for every 10 m² Proper provision for Disposal of Hazardous Material Staircase not arranged round a Lift Shaft Sealing of Various Shafts/Ducts at each floor Level with Fire Resistant Material DOCUMENTS TO Approved Fire Safety Layout Plan specting officer may also suggest further requires	D BE ATTACI	HED NO	Authority Ok or not
02. 03. 04. 05.	All Floors shall be suitably compartmented/Zone with area of each compartment being not more than 750 m² for non-sprinkled building/basement and 1800 m² for sprinkled building/basement Prohibition on storage of Flammable Liquid in Laboratories or in other area not more than 03 Liter for every 10 m² Proper provision for Disposal of Hazardous Material Staircase not arranged round a Lift Shaft Sealing of Various Shafts/Ducts at each floor Level with Fire Resistant Material DOCUMENTS TO	D BE ATTACI	HED NO	Authority Ok or not
02. 03. 04. 05.	All Floors shall be suitably compartmented/Zone with area of each compartment being not more than 750 m² for non-sprinkled building/basement and 1800 m² for sprinkled building/basement Prohibition on storage of Flammable Liquid in Laboratories or in other area not more than 03 Liter for every 10 m² Proper provision for Disposal of Hazardous Material Staircase not arranged round a Lift Shaft Sealing of Various Shafts/Ducts at each floor Level with Fire Resistant Material DOCUMENTS TO Approved Fire Safety Layout Plan specting officer may also suggest further requires	D BE ATTACI	HED NO	Authority Ok or not
02. 03. 04. 05.	All Floors shall be suitably compartmented/Zone with area of each compartment being not more than 750 m² for non-sprinkled building/basement and 1800 m² for sprinkled building/basement Prohibition on storage of Flammable Liquid in Laboratories or in other area not more than 03 Liter for every 10 m² Proper provision for Disposal of Hazardous Material Staircase not arranged round a Lift Shaft Sealing of Various Shafts/Ducts at each floor Level with Fire Resistant Material DOCUMENTS TO Approved Fire Safety Layout Plan specting officer may also suggest further requires	D BE ATTACI	HED NO	Authority Ok or not

(SIGNATURE OF THE APPLICANT)

Recommendations of the Inspection Officer					
Note: - the inspection officer should mention the deficiencies found during the inspection and copy of the					
report to be issued to the owner/occupier	Signature				
	Name of inspecting officer				
	Designation				
	Date of Inspection				
	Contact No				
RECEIPT					
Name of the Recipient					
Signature	Contact No				
Date of receipt//	E-Mail ID				